



FLEX MOUNT SYSTEM L.E.D. DOUBLE STACK NAVIGATION LIGHT SETS (2NM/5NM)

Flex Mount System

Figs. 1077 - 1080 Series L.E.D. Double Stack Navigation Lights

Certified For Use on Vessels 20 Meters (65.6 ft.) to 50 Meters (164.0 ft.) in Length



CONSTRUCTION:

- Black or White Polymer
- Pre-Wired with 3 Feet of 18/2-SO Cable
- Translucent color specific insert on top of light for easy identification
- Independent mounting bracket allows for easy interchange of light fixtures



Fig. 1077
Green & Red Side Lights



Fig. 1078
Masthead Light



Fig. 1079
Stern Light

Fig. 1079
Towing Light



Fig. 1080
All-Round Light

Double Stack Light Ordering Info

Black Polymer Description	Visibility Arc	Visibility Miles	120/240 VAC	12/24 VDC	Ship Wt. Carton Lbs. Standard Pkg.
			Black Polymer Std. Pkg. 1 Pc.	Black Polymer Std. Pkg. 1 Pc.	
Red Side Light	112-1/2°	2	1077R00BLK	1077R01BLK	7.5
Green Side Light	112-1/2°	2	1077G00BLK	1077G01BLK	7.5
White Masthead Light	225°	5	1078000BLK	1078001BLK	7.4
White Stern Light	135°	2	1079000BLK	1079001BLK	7.5
Yellow Towing Light	135°	2	1079M00BLK	1079M01BLK	7.5
White All-Round Light	360°	2	1080000BLK	1080001BLK	7.2
White All-Round Light**	360°	5	1080H00BLK	1080H01BLK	7.2
Red All-Round Light	360°	2	1080R00BLK	1080R01BLK	7.2
Green All-Round Light	360°	2	1080G00BLK	1080G01BLK	7.2
Yellow All-Round Light	360°	2	1080M00BLK	1080M01BLK	7.2

White Polymer Description	Visibility Arc	Visibility Miles	120/240 VAC	12/24 VDC	Ship Wt. Carton Lbs. Standard Pkg.
			White Polymer Std. Pkg. 1 Pc.	White Polymer Std. Pkg. 1 Pc.	
Red Side Light	112-1/2°	2	1077R00WHT	1077R01WHT	7.5
Green Side Light	112-1/2°	2	1077G00WHT	1077G01WHT	7.5
White Masthead Light	225°	5	1078000WHT	1078001WHT	7.4
White Stern Light	135°	2	1079000WHT	1079001WHT	7.5
Yellow Towing Light	135°	2	1079M00WHT	1079M01WHT	7.5
White All-Round Light	360°	2	1080000WHT	1080001WHT	7.2
White All-Round Light**	360°	5	1080H00WHT	1080H01WHT	7.2
Red All-Round Light	360°	2	1080R00WHT	1080R01WHT	7.2
Green All-Round Light	360°	2	1080G00WHT	1080G01WHT	7.2
Yellow All-Round Light	360°	2	1080M00WHT	1080M01WHT	7.2

Tech Info

- L.E.D.: Operates on 12/24 VDC or 120/240 VAC Systems
- No user serviceable parts
- Mounting screw size: 3/8"
- Height overall: 13-1/4"
- Vert. height upper*: 10-3/4"
- Vert. height lower*: 3-1/2"

MARINE NAVIGATION LIGHT CERTIFIED TO THE USCG AND '72 COLREGS BY IMANNA LABS IN ACCORDANCE WITH U.L. 1104 (A.B.Y.C. A-1104). FOR USE ON VESSELS 20 METERS TO 50 METERS.

Fig. 1381000BLK Bracket for mounting Double Stack lights.



* Vertical height is the measurement from the mounting surface to the center of the lens.

Special lights to meet local requirements are available upon request

**For Great Lakes use

Note: L.E.D.'s have no user serviceable parts