



PERKO® DOUBLE LENS NAVIGATION LIGHTS

Figs. 1364 - 1368 Series Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length



CONSTRUCTION:

- Lightweight But Durable Fiber-Filled Black Polymer
- Pre-Wired Medium Prefocus Socket
- Includes Two 3 Foot Lengths of 16/2-SO Cable Through Watertight Terminal Tubes
- Watertight Access Cap for Rebulbing and Cleaning
- Rough Service Bulbs are Available

Ordering Info				Tech Info	
Description	Visibility Arc	Visibility Miles	Std. Pkg. 1 Pc.	Ship Wt. Carton Lbs. Standard Pkg.	
Red Side Light	112-1/2°	3	1364REOBLK	7.0	Bulb: 24, 120 or 220 Volt (Not Included) Mounting Bolt Size: 3/8" Height Overall: 17-1/4" Height Lens: 6-3/4"
Green Side Light	112-1/2°	3	1364GEOBLK	7.0	
White Masthead Light	225°	6	1365E00BLK	6.9	
White Stern Light*	135°	3	1366E00BLK	6.9	
Yellow Towing Light	135°	3	1366ME0BLK	6.9	
White All-Round Light*	360°	3	1367E00BLK	6.3	
White All-Round Light**	360°	6	1367HE0BLK	6.3	
Red All-Round Light	360°	3	1368REOBLK	6.3	
Green All-Round Light	360°	3	1368GEOBLK	6.3	
Yellow All-Round Light	360°	3	1368ME0BLK	6.3	

Special lights to meet local requirements are available upon request

*These lights are supplied with a Gray Tinted Lens

**For Great Lakes use



Fig. 1364
Green Side Light



Fig. 1368
Red All-Round



Fig. 1366
Yellow Towing



Fig. 1367
White All-Round



Fig. 1364
Red Side Light

IMPORTANT BULB DATA
To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must be used with the following PERKO bulbs:
24 Volt Use Cat. No. 0342024CLR
120 Volt Use Cat. No. 0342004CLR or 0342RS4CLR when a "Rough Service" bulb is required.
220 Volt Use Cat. No. 0342220CLR.

SPARE PARTS ORDERING INFORMATION

Access Cap Assembly Including
Top Socket: 1363DBLCLK
Medium Prefocus Socket: 0367
Bulb Information:
24V = 0342024CLR
120V= 0342004CLR or 0342RS4CLR
220V= 0342220CLR

See Page C-36 for Bulb Information.