

Navigation Light Sets

2 Mile/5 Mile Certified (USCG 2nm/5nm)

Use on Power Driven Vessels 20m (65.6 ft.) to 50 m (164.0 ft.) in Length

Material: Black or White Polymer
Pre-Wired with 3 Feet of 16/3-SO Cable

Dimensions: Height: 7-1/2", Base: 5-9/32" x 5-9/32"

Screw Size: 1/4"

Voltage: 12, 24 or 120V (Bulb Not Included)

	<u>12V</u>	<u>24V</u>	<u>120V</u>
Wattage:	30 watts	30 watts	30 watts
Amperage:	2.5 amps	1.25 amps	.25 amps

Features: Watertight Access Cap for Rebulbing and Cleaning



Fig. 1128
Masthead Light



Fig. 1127
Red & Green Side Lights



Fig. 1129
Stern Light



Fig. 1129
Towing Light



Fig. 1130
All-Round Lights

Description	Visibility Arc	Visibility Miles	Black Std. Pkg.	White Std. Pkg.
Red Side Light	112-1/2°	2	1127RA0BLK	1127RA0WHT
Green Side Light	112-1/2°	2	1127GA0BLK	1127GA0WHT
White Masthead Light	225°	5	1128A00BLK	1128A00WHT
White Stern Light*	135°	2	1129A00BLK	1129A00WHT
Yellow Towing Light	135°	2	1129MA0BLK	1129MA0WHT
White All-Round Light*	360°	2	1130A00BLK	1130A00WHT
White All-Round Light**	360°	5	1130HA0BLK	1130HA0WHT
Red All-Round Light	360°	2	1130RA0BLK	1130RA0WHT
Green All-Round Light	360°	2	1130GA0BLK	1130GA0WHT
Yellow All-Round Light	360°	2	1130MA0BLK	1130MA0WHT

Special lights to meet local requirements are available upon request.

*These lights are supplied with a Gray Tinted Lens

**For Great Lakes use



Spare Parts Information

IMPORTANT BULB DATA
To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must use a PERKO Cat. No. 0374 bulb.

Lens Assemblies:
Red: 0249000RED
Green: 0249000GRN
White: 0249000CLR
Gray: 0249000GRY
Yellow: 0249000YLW



Fig. 0249

Required Bulbs:
12 Volt: 0374001CLR
24 Volt: 0374002CLR
120 Volt: 0374004CLR



Fig. 0374

Other Parts:
O-Ring for Cap: 1119
Double Contact Socket: 0134
Access Cap, O-Ring and Retainer:
Blk:1105000BLK or Wht:1105000WHT